

# Semi-Automatic Screen Filter

2", 2½" & 3"

## HIGHLIGHTS

- **Durable Polymer Body:** Chemically bonded for long-lasting strength.
- **Stainless Steel Mesh (SS-316):** Corrosion-resistant and reliable for consistent filtration.
- **Simple Cleaning Mechanism:** Handle rotation system allows for easy, online cleaning without stopping water flow.
- **Clogging Indicator:** Red button pops up when cleaning is needed based on pressure differential.
- **Multiple Connection Options:** Available in 2", 2½" & 3" BSP/NPT male thread connections.



## Technical Data

Filter Models Screen		AQ-524T-SA	AQ-525T-SA	AQ-526T-SA
Inlet /Outlet Connection		2"/50mm	2½"/65mm	3"/80mm
Connection Type		Threaded (BSP/NPT) / Grooved / Flanged		
*Maximum Flow Rate	M³/HR	25	30	40
	GPM	110	132	176
Maximum Working Pressure	BAR	PPGF – 8 / PAGF – 10		
	PSI	PPGF – 116 / PAGF – 145		
Filtration Surface Area (Screen)	CM²	800	800	1200
	INCH²	124	124	186
Minimum Flushing Pressure	BAR	1.5		
	PSI	22		
Filtration Degree (Screen)	Mesh	150 / 120 / 80		
	Microns	100 / 130 / 200		
Material of Construction		All Polymeric /NBR / St.St.		
Screen Material		St.St.		
Flush Port		2" – Male Threaded Port (with Flush valve)		